

KENWOOD

CA-PLT98RG2

XM160-2-98 AMPLIFIER MOUNTING PLATE DESIGNED AND
ENGINEERED FOR 1998-2013 HARLEY-DAVIDSON® NON-CVO ROAD
GLIDE® MOTORCYCLES

INSTRUCTION MANUAL

JVCKENWOOD Corporation

Important Notes

©2023 JVCKENWOOD Corporation. All Rights Reserved. KENWOOD® and eXcelon® are registered trademarks of JVCKENWOOD Corporation. Harley-Davidson®, Electra Glide®, Road Glide®, Street Glide®, Ultra Classic®, Tri Glide®, CVO™, Screamin Eagle® and Tour-Pak® are trademarks or registered trademarks of Harley-Davidson, Inc. and/or its affiliates and if used or implied are for reference only. There is no affiliation between Harley-Davidson, Inc. and/or its affiliates and JVCKENWOOD Corporation and/or its affiliates. All other trademarks are the property of their respective owners. Specifications subject to change without notice.

Take the time to read through this instruction manual.

Familiarity with installation and operation procedures will help you obtain the best performance from your new product.

XM160-2-98 Amplifier Mounting Plate Installation Instructions

■ Installation procedure

1. Using one of the supplied pieces of Velcro®, attach the amplifier to the plate as shown in Fig 1.1, noting that the amplifier will be upside down so the power harness is facing the front of the bike.
2. Using the second piece of Velcro, attach the amplifier/plate assembly to the brake side of the bike, making sure that the holes in the plate are lined up with the holes in the bottom of the fairing.

NOTE: The bolts that hold the turn signals in place will secure the plate even though the adhesive does most of the work.



Fig 1.1 - Amplifier mounted to plate on bike

For updated information (the latest Instruction Manual, etc.),
please visit the following website:

https://manual.kenwood.com/en_contents/search/

