

AX-HON24RVC-6V Honda (without touchscreen) 2015-up

INTERFACE FEATURES

- Retains the factory AUX-IN jack
- Retains the factory backup camera to an aftermarket radio
- Includes the AX-CAM6V 12-volt to 6-volt converter

INTERFACE COMPONENTS

- AX-HON24RVC-6V harness • AX-CAM6V 12-volt to 6-volt converter

APPLICATIONS

HONDA	
Fit	2015-up
Pilot	2016-up
Ridgeline	2017-up

TOOLS REQUIRED

- Wire cutter • Crimping tool • Solder gun • Tape
- Connectors (example: butt connectors, bell caps, etc.)

CAUTION! All accessories, switches, climate controls panels, and especially air bag indicator lights must be connected before cycling the ignition. Also, do not remove the factory radio with the key in the on position, or while the vehicle is running.



Connections to be made

- Connect the **Black** wire of the AX-CAM6V to chassis ground.
- Connect the **Red** wire labeled "Camera Power 6V" to the **Blue/Red** wire of the AX-CAM6V.
- Connect the reverse wire from the aftermarket radio, to the reverse signal in the vehicle, and also to the **Blue/White** wire of the AX-CAM6V.
- Connect the **Yellow** RCA jack to the rear camera input of the aftermarket radio.

IMPORTANT

If you are having difficulties with the installation of this product, please call our Tech Support line at **1-800-253-TECH**. Before doing so, look over the instructions a second time, and make sure the installation was performed exactly as the instructions are stated. Please have the vehicle apart and ready to perform troubleshooting steps before calling.



KNOWLEDGE IS POWER
Enhance your installation and fabrication skills by enrolling in the most recognized and respected mobile electronics school in our industry. Log onto www.installerinstitute.com or call 800-354-6782 for more information and take steps toward a better tomorrow.



Metra recommends MECP certified technicians