


For information about other American International automotive accessories visit our website at:  
<http://www.aius.net>



# HONK830 Mounting Kit



## VEHICLE APPLICATIONS

### **Honda**

1990-02 ACCORD  
1999-00 CIVIC  
\*2006-12 CIVIC  
2005 CIVIC SPECIAL EDITION  
1997-06 CRV  
2003-06 ELEMENT  
2007-11 ELEMENT LX  
1995-04 ODYSSEY  
2005-08 PILOT LX  
1989-01 PRELUDE

### **Acura**

1997-99 CL  
1990-01 INTEGRA  
1986-96 LEGEND  
1996-98 TL  
1992-94 VIGOR  
**Isuzu**  
1996-99 OASIS



2500 East Francis Street Ontario, CA 91761, U.S.A.  
USA Sales (800) 336-6500  
Canada Sales (888) 922-3006 • USA Fax (805) 388-7950

**CUSTOMER HELP LINE**  
USA 800-323-4329 • Canada 800-245-8777

iHONK830

\*Requires Dash Bezel HCB8800L/HCB8800D or HCB8820 for all Non-Navigation Equipped Vehicles.

©2015 AMERICAN INTERNATIONAL INDUSTRIES, INC.

TECH Ver. 01/15 PRINT Ver. 01/15

## KIT PREPARATION

### SINGLE DIN INSTALLATION

#### TOOLS REQUIRED:

- A. Razor knife, or file (to cut or file the removed mounting tabs flush with the back edge of the main bracket)
- B. Pliers, or wire cutters (for mounting tab removal)
- C. Phillips screwdriver (to attach side brackets to rear of pocket)


#### KIT PREPARATION:

1. Locate the HON-K830 main frame bracket.
2. Find the page that has the year and make of vehicle you are working on.
3. Locate the left and right side mounting brackets.
4. Following the illustration on the page for your vehicle, remove all mounting tabs from the main frame and file or trim flush with the rear edge of the main bracket.
5. Remove all mounting tabs from the left and right side brackets unless they are illustrated on your vehicle's instruction page.
6. Bend and remove the upper section from the left and right side mounting brackets, and file flush for all vehicles not listed below. See illustration below.
7. Insert the left and right side brackets into the opening of the main frame as shown in illustration C on page 2. Then insert and attach the pocket into the pocket opening and secure the side brackets to the rear of the pocket using the (2) small Phillips screws provided. (Pocket only fits one way)

#### \* ATTENTION:



Do not detach upper section of brackets for these vehicles

1998-02 Honda Accord  
2002-06 Honda CRV  
2003-11 Honda Element  
1999-04 Honda Odyssey  
2005-08 Honda Pilot LX





## VEHICLE SPECIFIC KIT PREPARATION

### 1999-04 HONDA ODYSSEY



Remove all shaded tabs shown above on left and right brackets.  
(Left bracket not shown)


### 2005 HONDA PILOT 2006-08 HONDA PILOT LX




### 2005-08 Honda Pilot LX Bracket Preparation

Remove all shaded tabs shown above on left and right brackets.  
(Left bracket not shown)

### 1989-91 HONDA PRELUDE





### 1997-01 HONDA PRELUDE




## VEHICLE SPECIFIC KIT PREPARATION

### 2002-06 HONDA CRV





View of radio cavity




Remove all shaded tabs shown above on left and right brackets.  
(Left bracket not shown)

### 2003-06 HONDA ELEMENT 2007-11 HONDA ELEMENT LX



Remove all shaded tabs shown above on left and right brackets.  
(Left bracket not shown)

### 1995-98 HONDA ODYSSEY 1996-99 ISUZU OASIS



POCKET MUST BE  
ON TOP

Remove all tabs not noted  
in illustration

## KIT PREPARATION

### SINGLE ISO INSTALLATION

#### TOOLS REQUIRED:

- A. Razor knife, or file (to cut or file the removed mounting tabs flush with the back edge of the main bracket)
- B. Pliers, or wire cutters (for mounting tab removal)
- C. Phillips screwdriver (to attach side brackets to rear of pocket & attach radio to brackets)




### KIT PREPARATION

1. Follow steps 1-7 on page 1.
2. Set the front of the kit face down on a clean work station.
3. Insert left and right ISO mount brackets into radio opening slots above the pocket as shown in illustration B & C below.
4. Place the radio between the ISO mount brackets.
5. Using the screws provided (screws may have to be shortened so they do not touch any internal components of radio) attach the radio to the side brackets loosely.
6. Set kit and radio upright and attach the ISO trim ring supplied with kit.
7. Adjust the radio forward for desired look and tighten mounting screws.

#### \* ATTENTION:

Do not detach upper section of brackets for these vehicles

1998-02 Honda Accord  
2002-06 Honda CRV  
2003-11 Honda Element  
1999-04 Honda Odyssey  
2005-06 Honda Pilot




## KIT PREPARATION



### SINGLE ISO INSTALLATION (cont.)

\* ATTENTION:  
Do not detach upper section of brackets for these vehicles

1998-02 Honda Accord  
2002-06 Honda CRV  
2003-11 Honda Element  
1999-04 Honda Odyssey  
2005-08 Honda Pilot LX





Attach IRB-830L & IRB-830R as shown in illustration when ISO mounting only in these vehicles






#### Single ISO Bracket Assembly For Vehicles Listed Below


90-97	Honda Accord
99-00	Honda Civic
06-12	Honda Civic
2005	Honda Civic Special Edition
97-01	Honda CRV
03-11	Honda Element
95-98	Honda Odyssey
05-08	Honda Pilot LX
89-01	Honda Prelude
97-99	Acura CL
90-00	Acura Integra
86-96	Acura Legend
96-98	Acura TL
92-94	Acura Vigor
96-99	Isuzu Oasis



### Vehicles w/side mounting brackets on factory radio




### Vehicles w/o side mounting brackets on factory radio





## VEHICLE SPECIFIC KIT PREPARATION

### 2005 HONDA CIVIC SPECIAL EDITION



### 1997-01 HONDA CRV






## 2006-12 HONDA CIVIC

### KIT PREPARATION

#### SINGLE ISO INSTALLATION


1. Set the front of the kit face down on a clean work station.
2. Insert Iso Spacers onto Left & Right mounting brackets. See Fig. B below.
3. Insert the left and right side brackets into the opening of the main frame as shown in illustration A & B below. Then insert and attach the pocket into the pocket opening and secure the side brackets to the rear of the pocket using the (2) small Phillips screws provided (Pocket only fits one way). See Fig. D below.
4. Place the radio between the ISO mount brackets.
5. Using the screws provided (screws may have to be shortened so they do not touch any internal components of radio) attach the radio to the side brackets loosely.
6. Set kit and radio upright and attach the ISO trim ring supplied with kit.
7. Adjust the radio forward for desired look and tighten mounting screws.
8. Insert HON-K830 kit with attached radio into Dash Bezel. Lead bottom edge of kit in first, then snap top in.




### DOUBLE ISO INSTALLATIONS

1. Follow steps 1-5 on page (1) of instruction booklet.
2. Using a pair of pliers, carefully bend and remove the ledge from the inside of the left and right mounting brackets, and file edge smooth. See Illustration A below.
3. Remove the rear pocket attachment bracket. See illustration A below.
4. Set the front of the main bracket face down on a clean work bench. Make sure you know which side is your top (see your vehicles instruction page) so you do not mount the radio components upside down in the kit.
5. Attach the left and right brackets to the kit as shown in illustration C below.
6. Place the radio components one at a time between the mounting brackets and using the screws provided (screws may have to be shortened so they do not touch any internal components of radio) and attach the radio components to the brackets loosely.
7. Set the kit with radio components upright, and attach the Double ISO trim ring to the front of the kit (NOTE: the trim ring will only attach one way).
8. Adjust the radio components forward for desired look, and tighten mounting screws.


#### HON-K830 MAIN TRIM RING



Vehicles w/side mounting brackets on factory radio



Vehicles w/o side mounting brackets on factory radio



## DOUBLE ISO INSTALLATIONS (Cont.)

**NOTE:** ISO mount screws are provided for your convenience. Always check depth inside ISO holes on radio to determine if screws must be cut shorter so they don't touch any electronic or mechanical parts on radio.

### \* ATTENTION:

**Do not detach upper section of brackets for these vehicles**

**1998-02 Honda Accord**


**2002-06 Honda CRV**

**2003-11 Honda Element**

**1999-04 Honda Odyssey**


**2005-08 Honda Pilot LX**

Remove all mounting tabs from the left and right side brackets unless they are illustrated on your vehicle's instruction page.



### Double ISO Bracket Assembly For Vehicles Listed Below

90-97	Honda Accord
99-00	Honda Civic
2005	Honda Civic special Edition
06-12	Honda Civic
97-01	Honda CRV
03-11	Honda Element
95-98	Honda Odyssey
05-08	Honda Pilot LX
89-01	Honda Prelude
97-99	Acura CL
90-00	Acura Integra
86-96	Acura Legend
96-98	Acura TL
92-94	Acura Vigor
96-99	Izusu Oasis




## 2006-12 HONDA CIVIC

### DOUBLE ISO/DOUBLE DIN INSTALLATIONS

1. Follow steps 1-4 on page 1 of the instruction booklet.
2. Using a pair of pliers, carefully bend and remove the ledge from the inside of the left and right mounting brackets, and file edge smooth. See Illustration A page 15.
3. Remove the rear pocket attachment bracket. See Illustration A page 15.
4. Set the front of the main bracket face down on a clean work bench. Make sure you know which side is your top so you do not mount the radio components upside down in the kit.
5. Insert ISO Spacers onto Left & Right mounting brackets. See Fig. B page 15.
6. Attach the left and right brackets to the kit as shown in Illustration C page 15.
7. Place the radio component(s) between the mounting brackets and using the screws provided (screws may have to be shortened so they do not touch any internal components of radio) and attach the radio component(s) to the brackets loosely.
8. Set the kit with radio component(s) upright, and attach the Double ISO trim ring to the front of the kit (NOTE: the trim ring will only attach one way).
9. Adjust the radio component(s) forward for desired look, and tighten mounting screws.
10. Insert kit into HON-K8800 Dash Bezel, lead bottom edge of kit in first, then snap top in.

## 2006-12 HONDA CIVIC

### HON-K830 MAIN TRIM RING



## 2006-12 Honda Civic

### KIT PREPARATION


#### SINGLE DIN INSTALLATION

#### KIT PREPARATION:


1. Locate the HON-K830 main frame bracket.
2. Locate the left and right side mounting brackets.
3. Following the illustration above, remove only the mounting tabs from the main frame (not marked with a letter) and file or trim flush with the rear edge of the main bracket.
4. Remove all mounting tabs from the left and right side brackets.
5. Insert the left and right side brackets into the opening of the main frame as shown in illustration E on page 15. Then insert and attach the pocket into the pocket opening and secure the side brackets to the rear of the pocket using the (2) small Phillips screws provided (Pocket only fits one way). See Fig. D page 15.

## VEHICLE SPECIFIC KIT PREPARATION


### 1996-98 ACURA TL




### 1990-93 HONDA ACCORD 1992-96 HONDA PRELUDE



### 1994-97 HONDA ACCORD




### 1998-02 HONDA ACCORD



**NOTE:** Attach rear support bracket to rear of pocket using (1) screw, included just prior to installing radio/kit assembly into dash.


## VEHICLE SPECIFIC KIT PREPARATION

### 1998-02 HONDA ACCORD



Remove all shaded tabs shown above on left and right brackets.  
(Left bracket not shown)

### 1999-00 HONDA CIVIC



## 1997-99 ACURA CL

### DASH DISASSEMBLY

1. Unsnap the dash panel and unplug the clock connector.
2. Remove (2) 8mm screws from the radio and unplug connectors and remove factory radio.

### 1990-93 ACURA INTEGRA

### DASH DISASSEMBLY

1. Remove (3) screws from the sides of the center console and remove the console.
2. Remove (2) screws holding the factory unit to the sub dash support bracket.
3. Remove the factory radio pocket from the dash cavity.

### 1994-01 ACURA INTEGRA

### DASH DISASSEMBLY

1. Using a panel tool pry outward on the cap under the emergency brake and remove. Remove the (2) screws in that area.
2. Remove (1) screw from each rear corner of the lower console and remove.
3. Remove the ashtray and the (2) screws from the rear of that area.
4. Unsnap the housing and unplug the connectors and remove the housing. Remove the shifter and unsnap the trim piece.
5. Remove (1) screw from each rear corner of the upper console and (2) screw from below the radio opening.
6. Remove the console bezel.
7. Remove (2) 8mm screws holding the factory radio in place.
8. Disconnect the connector and remove radio.

### 1986-89 ACURA LEGEND

### DASH DISASSEMBLY

1. Remove the front console trim.
2. Remove the (6) screws securing the radio/center panel to the sub-dash.
3. Disconnect the wire harnesses connected to the radio and lighter and unplug the antenna lead, and remove the radio/panel.
4. Remove the (2) screws securing the factory radio to the panel assembly, and remove the radio.

### 1990-96 ACURA LEGEND

### DASH DISASSEMBLY

1. Remove (2) screws below the ashtray and unclip the dash panel.
2. Unplug the lighter and remove the panel.
3. Remove the (2) screws holding the rear of the factory radio to the sub dash.
4. Unplug radio connector and remove radio.

## 1996-98 ACURA TL

### DASH DISASSEMBLY

1. Starting from the bottom, carefully unclip and remove the trim bezel from around radio and climate controls.
2. Unplug the wire harnesses for the climate control and rear defroster and remove the trim bezel.
3. Remove the (4) Phillips screws securing the factory radio/trim bezel to the sub-dash.
4. Carefully pull radio forward, disconnect wire harness(s) and antenna lead and remove radio/trim bezel assembly.
5. Loosen the (2) Phillips screws securing the back of the factory radio to the metal frame, and remove radio.

## 1992-94 ACURA VIGOR

### DASH DISASSEMBLY

1. Remove the access cap from the climate control and (1) screw from there.
2. Unsnap the cluster and remove (2) screws from the ashtray area.
3. Remove each cap and screw from the front of the console.
4. Remove (2) screws from the storage compartment and remove it.
5. Unsnap the dash panel and unplug the connectors.
6. Remove (2) 8mm screws from the rear of the factory radio and unplug radio connector and remove radio.

## 1990-93 HONDA ACCORD

### DASH DISASSEMBLY

1. Open console lid and remove the mat and base cover.
2. Remove (4) screws from the bottom area of the center console.
3. Remove the shifter knob and remove console out.
4. Remove (2) screws holding the rear of the radio in place and remove radio enough to unplug radio connectors and antenna plug.

## 1994-97 HONDA ACCORD

### DASH DISASSEMBLY

1. Slide drivers and passengers seat forward, and then remove (2) screws one on each side of the console.
2. Remove ashtray and remove (1) screw from ashtray area.
3. Open center console and remove cover plate on the bottom of console cavity. Remove (2) screws holding center console in place.
4. Remove drink holder & remove (1) Phillips screw that is angled downward at the front edge of the console.
5. After all the screws have been removed slide console back about 3" and then remove (2) screws holding radio trim bezel in place.
6. Pull gently on radio trim panel to unsnap and then unplug hazard switch and also the clock connector.
7. Remove (2) 8mm screws holding the rear of the radio in place and then slide radio out enough to unplug radio connectors and antenna plug and remove radio.

## 1996-99 ISUZU OASIS


### DASH DISASSEMBLY

7. Carefully pull back on the lower console assembly to unplug the harnesses and remove console.
8. Remove the (2) Phillips screws securing each side of the drink tray and remove drink tray.
9. Remove the (2) 5/16 screws securing the factory radio to the sub-dash (located below the radio at the rear).
10. Carefully pull radio forward, disconnect wire harness and antenna lead and remove radio.


## VEHICLE SPECIFIC KIT PREPARATION

### 1997-99 ACURA CL


### 1992-94 ACURA VIGOR



### 1990-01 ACURA INTEGRA



## 1986-96 ACURA LEGEND



## 1989-91 HONDA PRELUDE

### DASH DISASSEMBLY

1. Remove the (4) phillips screws securing the radio mounting trim bezel to the radio bracket assembly.
2. Remove the (1) phillips screw from each side of the sub-dash securing the radio/trim bezel assembly to the sub-dash.
3. Disconnect ashtray and lighter harnesses from the dash console, and pull radio assembly forward.
4. Disconnect all harnesses from the radio/console assembly and remove.
5. Remove the (2) phillips screws securing the factory radio to the mounting bracket assembly.
6. Remove the (1) phillips screw securing the factory pocket to the radio bracket assembly and remove pocket.

## 1990-93 HONDA ACCORD

## 1992-96 HONDA PRELUDE

### DASH DISASSEMBLY

1. Remove (2) screws above the radio area top of the console.
2. Remove four (4) screws from the side of the console area.
3. Move console enough to get to the (2) screws holding the shifter bracket to the console.
4. Remove four(4) screws holding the radio trim panel and then remove the radio assembly.

## 1997-01 HONDA PRELUDE

### DASH DISASSEMBLY

1. Using a panel tool carefully pry upward on the radio dash bezel and remove
2. Remove (2) screws holding the radio sub dash piece in place and remove
3. Remove (4) screws holding the radio to the radio sub dash.
4. Reinstall the factory sub radio dash section and snap in the HONK-831

## 1996-99 ISUZU OASIS

### DASH DISASSEMBLY

1. Open the glove box door and remove the single plastic/rubber retainer stoppers on each side of the glove box.
2. Remove the (1) Phillips screw from the retaining arm on the right side of the glove box and lower glove box down out of the way.
3. Remove the (2) Phillips screws the bottom of the center console just above the carpet.
4. Remove the (2) Phillips screws from the right side of the center console.
5. Open the console storage pocket and remove the (2) Phillips screws from the upper section.
6. Remove the (2) Phillips screws from the under-dash panel on the drivers side and pop out the right side to allow removal of the (1) Phillips screw on the left side of the center console.

(CONTINUED on Page 12.)

## 1998-02 HONDA ACCORD

### DASH DISASSEMBLY

1. Gently pry out on the clock, unplug the harness and remove.
2. Remove the (1) Phillips screw at the rear of the clock cavity.
3. Remove the (2) Phillips screws from the bottom of the radio trim bezel.
4. Gently pull forward on the radio trim bezel (NOTE: there is a snap clip on each side of the trim beside the radio). Disconnect the wire harnesses and remove the trim panel.
5. Remove the (4) Phillips screws holding the radio in place, disconnect the wire harness and antenna lead and remove.

## 1999-00 HONDA CIVIC

### DASH DISASSEMBLY

#### STEP 1

1. Remove the (2) phillips screws from the bottom edge of the glove box door and remove the door.
2. Remove the (3) phillips screws from the panel below the steering wheel column.
3. Gently pull down on the on steering wheel lower panel and remove.
4. Remove the (2) phillips screws from under the climate controls.
5. Remove the (4) phillips screws from the lower dash area.
6. Remove the (4) phillips screws holding the bottom of the trim bezel/radio assembly and gently pull out as far as you can.
7. Carefully cut the wire ties holding the climate control and radio wiring.
8. Carefully pull forward on the trim and radio assembly and remove from the dash cavity.
9. Disconnect all wiring.

#### STEP 2

1. Remove the (3) screws holding the climate controls to the dash bezel and remove the controls.
2. Remove the (4) phillips screws holding the radio assembly to the back of the bezel.
3. Remove the (4) phillips screws holding the factory brackets to the radio.
4. Slide the radio out through the front of the trim bezel.

## 1994-97 HONDA ACCORD

### DASH DISASSEMBLY

1. Slide drivers and passengers seat forward, and then remove (2) screws one on each side of the console.
2. Remove ashtray and remove (1) screw from ashtray area.
3. Open center console and remove cover plate on the bottom of console cavity. Remove (2) screws holding center console in place.
4. Remove drink holder & remove (1) Phillips screw that is angled downward at the front edge of the console.
5. After all the screws have been removed slide console back about 3" and then remove (2) screws holding radio trim bezel in place.
6. Pull gently on radio trim panel to unsnap and then unplug hazard switch and also the clock connector.
7. Remove (2) 8mm screws holding the rear of the radio in place and then slide radio out enough to unplug radio connectors and antenna plug and remove radio.

## 1998-02 HONDA ACCORD

### DASH DISASSEMBLY

1. Gently pry out on the clock, unplug the harness and remove.
2. Remove the (1) Phillips screw at the rear of the clock cavity.
3. Remove the (2) Phillips screws from the bottom of the radio trim bezel.
4. Gently pull forward on the radio trim bezel (NOTE: there is a snap clip on each side of the trim beside the radio). Disconnect the wire harnesses and remove the trim panel.
5. Remove the (4) Phillips screws holding the radio in place, disconnect the wire harness and antenna lead and remove.

## 1999-00 HONDA CIVIC

### DASH DISASSEMBLY

#### STEP 1

1. Remove the (2) phillips screws from the bottom edge of the glove box door and remove the door.
2. Remove the (3) phillips screws from the panel below the steering wheel column.
3. Gently pull down on the on steering wheel lower panel and remove.
4. Remove the (2) phillips screws from under the climate controls.
5. Remove the (4) phillips screws from the lower dash area.
6. Remove the (4) phillips screws holding the bottom of the trim bezel/radio assembly and gently pull out as far as you can.
7. Carefully cut the wire ties holding the climate control and radio wiring.
8. Carefully pull forward on the trim and radio assembly and remove from the dash cavity.
9. Disconnect all wiring.

#### STEP 2

1. Remove the (3) screws holding the climate controls to the dash bezel and remove the controls.
2. Remove the (4) phillips screws holding the radio assembly to the back of the bezel.
3. Remove the (4) phillips screws holding the factory brackets to the radio.
4. Slide the radio out through the front of the trim bezel.

## 2003-06 HONDA ELEMENT

### 2007-11 HONDA ELEMENT LX

### DASH DISASSEMBLY

1. Unclip trim bezel from around radio. There are (2) slots on the bottom of the trim bezel.
2. Remove the (4) 8mm bolts securing factory radio to the sub-dash.
3. Pull radio forward, disconnect wire harness and antenna lead, and remove radio.

## 1995-98 HONDA ODYSSEY

### DASH DISASSEMBLY

1. Open the glove box door and remove the single plastic/rubber retainer stoppers on each side of the glove box.
2. Remove the (1) Phillips screw from the retaining arm on the right side of the glove box and lower glove box down out of the way.

## 1999-04 HONDA ODYSSEY

### DASH DISASSEMBLY

1. Gently pry outward on radio trim bezel.
2. Disconnect all harnesses and remove.
3. Remove (4) Phillips screws that secure the radio.
4. Slide radio forward.
5. Disconnect wire harness and antenna lead.
6. Remove radio.

## 2005 HONDA PILOT

### DASH DISASSEMBLY

1. Carefully pry outward on the trim bezel from around the radio.  
**NOTE:** There are 4 panel clips holding the factory trim bezel in place, (2) are located 1/2 inch down from the top on each side of the trim bezel, (2) are located 1 inch in from each corner on the bottom of the trim bezel. There are cut-out slots on the trim bezel at each of these locations to allow a thin flat-blade screwdriver to pry outward on the trim bezel.
2. Disconnect the harnesses from the trim bezel and remove bezel.
3. Remove the (4) phillips screws securing the radio to the sub-dash.
4. Pull radio forward, disconnect the wire harnesses and antenna lead and remove radio.

## 2006-08 HONDA PILOT LX

### DASH DISASSEMBLY

1. Remove the (2) phillips screws above the instrument gauges, Lower the steering column down and carefully pry the instrument gauge trim panel forward and remove trim.
2. Engage the parking brake and put the key in the ignition, turn the key to the on position and depress the brake pedal and lower the shift lever down.
3. Remove the Trim panel located to the left of the radio/vent bezel.
4. Carefully pry the radio/Vent trim bezel forward, disconnect the attached harnesses and remove bezel.
5. Remove the (4) phillips screws securing the radio to the sub-dash, pull radio forward, disconnect all harnesses and antenna lead and remove radio.

## 1989-91 HONDA PRELUDE

### DASH DISASSEMBLY

1. Remove the (2) phillips screws from the bottom edge of the climate controls.
2. Remove the (3) phillips screws from each side of the center console.
3. Set the emergency brake.
4. Remove the (1) plastic beauty cap from the end of the center console and remove the (2) phillips screws from this location.
5. Carefully pull the rear console section back and remove.
6. Place the gear shift lever all the way to the rear position.
7. Carefully slide front center console section back and remove.  
(CONTINUED on Page 11.)