

For information about other American International automotive accessories visit our website at:

<http://www.americaninternational.net>



**American  
International**  
*Car Stereo Installation Kits & Accessories*

## DASH DISASSEMBLY INSTRUCTIONS

1. Remove the ashtray. Remove (1) screw from the top-right corner of the ashtray cavity.
2. Remove (2) Phillips screws above the climate controls.
3. Remove (2) Phillips screws from below the radio. Unsnap the bezel and disconnect the cigarette lighter.
4. Remove (4) screws securing the radio to the sub-dash.
5. Carefully pull the radio forward, disconnect the wire harness and antenna lead and remove radio.

## RADIO INSTALLATION INSTRUCTIONS

**NOTE:** Requires new radio's metal sleeve

1. Insert DIN metal-sleeve from your new radio into the radio opening of the installation kit.
2. Depress the tabs from inside the sleeves opening upward, outward, and downward to secure sleeve to the installation kit.
3. Slide new radio through DIN metal-Sleeve until it locks in place.



**NDK770 Mounting Kit**

**Automotive Products Division**  
1040 Avenida Acaso • Camarillo, CA 93012, U.S.A.  
USA Sales (800) 336-6500  
Canada Sales (888) 922-3006 • USA Fax (805) 388-7950

**CUSTOMER HELP LINE**  
USA 800-323-4329 • Canada 800-245-8777

iNDK770

## VEHICLE APPLICATIONS

**Nissan**  
1986-93 HARDBODY TRUCK  
1986-93 PATHFINDER