



# EXM8SN / 500 WATTS

8" NEODYMIUM SERIES MIDRANGE

## **FEATURES**

- 2.0" (51mm) Voice Coil
- Neodymium 10 Piece Radially Equalized Magnet Assembly
- IP52 Rated Paper Cone With Treated Cloth Surround
- Heavy Gauge Steal Stamped Basket

#### **SPECIFICATIONS**

- Power Handling: 300 Watts
- Dynamic Wattage: 600 Watts
- Frequency Response: 85Hz 11KHz
- Sensitivity (1w/1m): 99.6dB
- Impedance: 4Ω

## **DIMENSIONS**

Mounting Depth: 3.43"/ 87mmCutout diameter: 7.13"/ 181mm

## THIELE-SMALL PARAMETERS

<ul><li>Resonant Frequency (fs)</li></ul>	71.8Hz
<ul><li>D.C. Voice coil resistance (RE)</li></ul>	3.3Ω
<ul><li>Mechanical Quality Factor (Qms)</li></ul>	4.02
<ul><li>Electrical Quality Factor (Qes)</li></ul>	0.39
<ul><li>Total Quality factor (Qts)</li></ul>	0.36
<ul><li>Equivalent Air Volume to Cms (Vas)</li></ul>	24.4L
<ul><li>Mechanical Compliance (Cms)</li></ul>	0.36 mm/N
<ul><li>Sensitivity (1W/1M)</li></ul>	99.6dB







